

This Page Is Inserted by IFW Operations
and is not a part of the Official Record

BEST AVAILABLE IMAGES

Defective images within this document are accurate representations of the original documents submitted by the applicant.

Defects in the images may include (but are not limited to):

- BLACK BORDERS
- TEXT CUT OFF AT TOP, BOTTOM OR SIDES
- FADED TEXT
- ILLEGIBLE TEXT
- SKEWED/SLANTED IMAGES
- COLORED PHOTOS
- BLACK OR VERY BLACK AND WHITE DARK PHOTOS
- GRAY SCALE DOCUMENTS

IMAGES ARE BEST AVAILABLE COPY.

As rescanning documents *will not* correct images,
please do not report the images to the
Image Problem Mailbox.

BEST AVAILABLE COPY



Deutsches Patent- und Markenamt

DEPATISr

Bibliographic data

Document JP0006100880AA (Pages

Criterion Field Contents

Title	TI	[] LUBRICATING COMPOSITION
Applicant	PA	ASAHI DENKA KOGYO KK
Inventor	IN	KAMAKURA TAMIJI ; TANAKA NORIYOSHI ; FUKUSHIMA ARITOSHI ; NANIWA KIMIYOSHI ; TATSUMI YUKIO ; MORITA KAZUHISA
Application date	AD	18.09.1992
Application number	AN	249857
Country of application	AC	JP
Publication date	PUB	12.04.1994
Priority data	PRC PRN PRD	
IPC main class	ICM	C10M 163/00
IPC subclass	ICS	C10M 159/12
IPC additional information on description	ICA	
IPC index class	ICI	(C10M 163/00, C10M 159:12, C10M 137:08, C10M 135:00, C10M 137:04) ; (C10M 159/12, C10M 125:10, C10M 133:04) ; C10N 10:12 ; C10N 30:00 ; C10N 30:06 ; C10N 40:04 ; C10N 40:25 ; C10N 50:10
Abstract	AB	PURPOSE: To obtain a lubricating composition excellent in frictional and wear characteristics by incorporating a specified molybdenum compound, acidic phosphoric ester (amine salt) and sulfurized compound each in a specified amount into a base oil or base grease. CONSTITUTION: This composition is obtained by mixing 100 pts.wt. base oil or base grease with 0.01-10 pts.wt. oil-soluble molybdenum compound obtained by reacting at least one hexavalent molybdenum compound selected from MoO_3 , H_2MoO_4 and an alkali salt (including an ammonium salt) thereof with an aromatic compound of formula I (wherein R_1 and R_2 are each H or a 1-30C hydrocarbon group except for the case where all of them are H at the same time, provided that the total of the number of carbon atoms thereof is 4 to 60), 0.1-10 pts.wt. acidic phosphoric ester (amine salt) consisting of 100-20mol% acidic phosphoric ester of formula II (wherein R_3 and R_4 are each H or a 4-20C hydrocarbon group except for the case where all of them are H at the same time) and 0-80mol% amino compound of formula III (wherein R_5 and R_6 are each H or a 4-30C hydrocarbon group except for the case where all of them are H at the same time), and 0.1-10 pts.wt. sulfur compound (e.g. a sulfurized olefin). COPYRIGHT: (C)1994,JPO&Japio

JP-A-06-160,880A

Appl 12, 1994



PATENT ABSTRACTS OF JAPAN

(11) Publication number: **06100880 A**(43) Date of publication of application: **12.04.94**

(51) Int. Cl.

C10M163/00
C10M159/12
///(C10M163/00 , C10M159:12 ,
C10M137:08 , C10M135:00 , C10M137:04
), (C10M159/12 , C10M125:10 ,
C10M133:04)
C10N 10:12
C10N 30:00
C10N 30:06
C10N 40:04
C10N 40:25
C10N 50:10

(21) Application number: **04249857**(22) Date of filing: **18.09.92**(71) Applicant: **ASAHI DENKA KOGYO KK**

(72) Inventor:
KAMAKURA TAMIJI
TANAKA NORIYOSHI
FUKUSHIMA ARITOSHI
NANIWA KIMIYOSHI
TATSUMI YUKIO
MORITA KAZUHISA

(54) LUBRICATING COMPOSITION

(57) Abstract

PURPOSE: To obtain a lubricating composition excellent in frictional and wear characteristics by incorporating a specified molybdenum compound, acidic phosphoric ester (amine salt) and sulfurized compound each in a specified amount into a base oil or base grease.

CONSTITUTION: This composition is obtained by mixing 100 pts.wt. base oil or base grease with 0.01-10 pts.wt. oil-soluble molybdenum compound obtained by reacting at least one hexavalent molybdenum compound selected from MoO_3 , H_2MoO_4 and an alkali salt (including an ammonium salt) thereof with an amino compound of

formula I (wherein R_1 and R_2 are each H or a 1-30C hydrocarbon group except for the case where all of them are H at the same time, provided that the total of the number of carbon atoms thereof is 4 to 60), 0.1-10 pts.wt. acidic phosphoric ester (amine salt) consisting of 100-20mol% acidic phosphoric ester of formula II (wherein R_3 and R_4 are each H or a 4-20C hydrocarbon group except for the case where all of them are H at the same time) and 0-80mol% amino compound of formula III (wherein R_5 and R_6 are each H or a 4-30C hydrocarbon group except for the case where all of them are H at the same time), and 0.1-10 pts.wt. sulfur compound (e.g. a sulfurized olefin).

COPYRIGHT: (C)1994,JPO&Japio

BEST AVAILABLE COPY

Japanese Laid-Open Patent Publication (Kokai) No. 100880/94

Laid Open: April 12, 1994

Japanese Patent Application No. 249857/92

Filed : September 18, 1992

Inventors : T. Kamakura et al.

Applicant : Asahi Denka Kogyo K.K.

Title of Invention: Lubricating Compositions

Claim

1. A lubricating composition comprising:

(a) 0.01 to 10 parts by weight of an oil-soluble molybdenum compound obtained by reacting one or more hexavalent molybdenum compounds selected from molybdenum trichloride and molybdic acid or alkali salts thereof (including ammonium salts) with an amino compound represented by the following general formula (1),



wherein R_1 and R_2 denote hydrogen atoms or the same or different saturated or unsaturated hydrocarbon radicals having 1 to 30 carbon atoms, but all of them are not hydrogen atoms at the same time, and the total number of carbon atoms of R_1 and R_2 is from 4 to 60;

(b) 0.1 to 10 parts by weight of an acid phosphate (amine salt) composed of 100 to 20 mol % of an acid phosphate represented by the following general formula (2) and 0 to 80 mol % of an amino compound represented by the following general formula (3),



wherein R_3 and R_4 denote hydrogen atoms or the same or different saturated or unsaturated hydrocarbon radicals having 4 to 20 carbon atoms, but all of them are not hydrogen atoms at the same time,



wherein R_1 and R_2 denote hydrogen atoms or the same or different saturated or unsaturated hydrocarbon radicals having 4 to 30 carbon atoms, but all of them are not hydrogen atoms at the same time; and

(c) 0.1 to 10 parts by weight of a compound containing sulfur, relative to 100 parts by weight of a base oil or base grease.

Detailed Description of the Invention

..... (omitted)

BEST AVAILABLE COPY